


Horizontal Rotator

DynaCool (D310) / PPMS (P310) / VersaLab (V310)

Probing the angular dependence (i.e. anisotropy) of the electrical resistance provides key insights into the electronic and crystallographic properties of materials. The Horizontal Rotator enables a sample to be rotated over 360° in the presence of an applied magnetic field spanning the entire temperature range of the base system. An automated indexing procedure and encoder ensures accurate angular positions and the on-board thermometer monitors the temperature in close proximity to the sample.



Angular dependence of magnetoresistance measured at 300 K and 1 T using the Resistivity Option in conjunction with the Horizontal Rotator. The 10 nm thick Permalloy film exhibits the expected anisotropic magnetoresistance (AMR) response.

Horizontal Rotator Specifications

Angle [Θ]

Range: -10° to 370°

Angular Step Resolution*: 0.0133°/step (standard resolution)

0.0011°/step (high resolution)

Orientation: Axis of rotation perpendicular to magnetic

field axis and puck key

Backlash: < 10°

Operational Range 1.8 to 400 K; 0 to 16 T

www.qdusa.com | sales@qdusa | Re: 1084-500 Rev. A2

*Specified resolution is only obtained by driving successive steps in the same direction.

Specifications are subject to change without notice.

Key Features:

- Integrated temperature sensor is in direct contact with the installed sample holder
- Materials chosen to minimize magnetic and temperature effects to ensure reproducibility upon cycling environmental parameters
- Two types of sample boards provided one where the rotation axis remains in the sample plane, and one where the axis points out of the sample plane
- Two channels per sample board, each channel provides 4-probe electrical contacts
- Low- and high-resolution motor options available

